
THREAD BREAKAGE DETECTOR


When Needle thread is broken, TBD makes a Sewing Cycle stop all at once.





《 OPTION 》

OPTIONAL GAUGE 1 set
PATTERN SOFT 1 unit
MEMORY LOADER 1 unit



[MEMORY LOADER]

PROGRAMMABLE Max. 20 PATTERNS

Appearance & Specifications changeable for Modification ---without Notice!



DEVICES]

- "XY" STEPPING MOTOR
- STANDARD PATTERN GAUGE & SOFT
- NEEDLE FOOT PRESSER
- PROGRAMMABLE SOFT
- "LED" TOUCHPANEL
- STACKER
- T.B.D.
- BOBBIN THREAD COUNTER
- AIR GUN
- CASTER (w/2 BRAKES)

SPECIFICATIONS]

SEWING HEAD JUKI DDL-9000B (SINGLE NEEDLE LOCK-STITCH w/TRIMMER)

NEEDLE STROKE

35mm

■ NEEDLE

DPX17 #12 ~ #14

■ MACHINE SPEED

MAX 5,000rpm

STITCH LENGH

FREE

■ SEWING SIZE

AVAILABLE SMALLEST

MAX 140mm X 160mm

PROGRAM PATTERNS

MAX 12

TABLE HEIGHT

930mm

POWER SUPPLY

200V/AC 650VA

AIR SUPPLY

0.4MPa 3 \$/min

■ FLOOR SPACE

L/1,200 X W/1,200 X H/1300

YUHO SEWING MACHINE CO., LTD

5-chome 3-1, Biwajima, Nishi-ku, Nagoya, Tel: +81-52-522-6276 Fax:+81-52-531-9270

e-mail: yoshihiro-ohtani@yuhomac.com

URL: http://www.yuhomac.com



NEW F E TYPE KNIT POCKET SETTER MODEL U-3206-E/1416





PATENTED YUHO ORIGINALLY DESIGNED KNIT POCKET SETTER-U-3206-E/1416 IS NOW UNVEILED !!

TOP FEATURED POINT ALLOWS TO FOLD AND ATTACH THE POCKETS SUCH VERY DIFFICULT FABRICS AS "STRETCHY KNITTED" EASILY, AUTOMATICALLY, NEVERTHLESS THE EXTREMELY LOWER COST OF PATTERN GAUGE THAN THE OTHER POCKET SETTERS.

ADDITIONALLY, AVAILABLE TO MAKE THE SMALLER SIZE, THE DOUBLE-STITCH SEWING



YUHO SEWING MACHINE

NEW F E J TYPE KNIT POCKET SETTER MODEL U-3206-E/1416




MONO-FRAMED POCKET FORMING

With originally designed Mono-framed Pattern Sewing, Pocket-piece forming is allowed accurately against the difficult fabrics.

Pocket-piece is folded in the Pattern Gauge, and sandwiched with Presser Pat tightly.

Pattern Sewing is allowed accurately synchronized with the Machine Presser holding down.

Particularly, very advantageous point is -----the fabric against Iron Pressing or Folding---





AVAILABLE "DOUBLE-STITCHING" & THE SMALLEST SIZE POCKET ATTACHING

Available "Double-stitching" simply such as "Stretchy Knit fabric" without Extra Charge!!

Particularly, Round Corner "Double-stitching" is required a lot of Skill and Handling Time. This unit promises high productivities even to all of the Beginners.

Additionally, available to the smallest size Pocket sewing---without Extra charge !!.



TWO UNITS OPERATION BUT SINGLE OPERATOR ALLOWED

Available to operate two different working process with Single Operator--- due to "overlapped working---loading ~ stacking " automatically. When a lot of production, Single Operator is allowed to operate 2 units---even if one is out of order, production can keep half of lot. This is very serious management in the factories !!.





SIMPLIFIED BUT ACCURATE POCKET SETTING

Available to enter the designed Patterns and to make the Pattern Correction to the Stitch-margin. Also, available to correct the one-side margin or Expansion or Deduction----available with "LED" Touch Panel simply.

With "Memory Loader", additional Pattern is allowed to enter freely---- [OPTION]



FREE FROM THREAD BREAKAGE WITH TAPE FOR KNIT FABRIC

Thread breakage can be free from the Strechy fabrics such as Knitted fabrics when inserting thinner Tape.

Tape is enough to set on the Pocketbottom part.



HIGH ACCURACY, HIGH DURABILITY PROMISES BEST PATTERN SEWING

"XY" Feeding Mechanism maintains by the finest and high durable Lineaway with the 2 Top/Bottom stage
Sewing Head is equiped with JUKI DDL-9000B Direct Drive. With Long-arm Head, loading space is enlarged extremely. With Operation working improvement, Consistent Quality, Skilless, High-Productivities are promised.



SIMPLIFIED GAUGE CONVERSION

Pattern Gauge conversion is allowed a few minutes by the Beginners. This is advantageous to the wide variation to Pocket Type and Fabrics. NO adjustment is allowed!!



FUNCTIONAL STACKER

With functional Stacker, "Over-lapped " working is allowed and promises 2 units operation by Single operator only.

VARIATION TO MAINTENANCE

NO asdjustment is allowed when Tilting or Tilting back

For Safety operation, Test sewing, Device Step checking are programmed on the "LED" Touch Panel---free from the Troubles.