« OPTION »

OPTIONAL PATTERN GAUGE

1 set

■ VACUUMED TABLE

1 set

■ OPTIONAL POCKET SETTER MODE 1 set



T.B.D. (THREAD BREAKAGE DETECTOR)

detects thread broken completely, and prevents working fail in advance



[SPECIFICATION]

MACHINE HEAD

JUKI DDL-9000B

MACHINE SPEED

4,000rpm

SEWING AREA

HEIGHT 120mm WIDE 100mm

• NEEDLE

DP X 134 #14

NEEDL STROKE

35mm 30pattern

PROGRAMMABLE PATTERN "XY" FEEDER

STEPPING MOTOR 2 AXIS

DISTANCE SETTING TO

500mm

SEWING POWER SUPPLY

200V/AC 510VA

AIR SUPPLY

5kg/cm 10n /min

FLOOR SPACE

 $L/1,200 \times W/900 \times H/1,500$ mm

[MAIN DEVICES]

- VERTICAL FOLDER
- STEPING MOTOR "XY" FEEDER
- OPTIONAL PATTERN GAUGE
- **BOBBIN THREAD TAKE-UP**
- PATTERN FOLDER
- NEEDLE FOOT PRESSER
- "LED" TOUCH PANEL
- **♦** ROTATOR STACKER
- ◆ T.B.D.
- **♦** BOBBIN COUNTER
- ◆ AIR GUN
- ◆ CASTER (w/BRAKE)

[DAILY OUTPUT]

1 cycle

12sec. 1,950pcs per 8H (20% ALLOWANCE)

(variable to Size & Sewing-End Mode))

YUHO SEWING MACHINE CO., LTD.

5-chome 3-1, Biwajima, Nishi-ku, Nagoya, Tel: +81-52-522-6276

Fax: +81-52-531-9270 e-mail: yuho@yuhomac.com http://www.yuhomac.com



NEW [E] TYPE NEW COIN POCKET SETTER MODEL U-3304-E





NEW COIN POCKET SETTER U-3304-E IS NEWLY MODIFIED TO EQUAL TO U-3103-e POCKET SETTER FUNCTION · · · PROMISING HIGH-CONSISTENT POCKET TOP-STITCHING !!

With newly designed STEEL LOADING TABLE, Precision and Durability is extremelygrade up!!

With Direct-Drive Machine Head JUKI DDL-9000B, Highly Consistent Sewing is promised greatly !!



YUHO SEWING MACHINE

NEW FE TYPE NEW COIN POCKET SETTER MODEL U-3304-E





CORNER STICKING OUT FREE

YUHO originally designed FOLDER promises "Free from Pocket-Corner Stitcking out" completely when folding.

PROMISING SKILLESS & HIGH PRODUCTIVITY

Place a Pocket bag on the Loading Table and set Pocket piece on the Plate. With Start Pedal ON, **3** corners of Pocket piece is folded automatically and traveled to the Needle point---saves "IRON PRESSING" completely.

Folded Pocket piece under the Needle is stitched accurately and stacked on completely with Rotate Stacker.

Setting-Stitching-Stacking---<u>3 Stage System</u> allows "Overlapped working"---promises High Productivities and Consistent Coin-Pocket attaching is promised.





PROVIDING LESS COST BUT HIGH FUNCTIONAL POCKET ATTACHING

Equiped with <u>JUKI DDL-9000B Direct Drive</u> Sewing Head with Long-arm, working space is allowed to 500mm widely.

Machinery Function is improved extremely with Thread-tension, Take-up---provides Highly Consistent Stitching finish. Particularly, Quick-acceleration, Quick-slowdown, High speed sewing, etc --- are grade up.

YUHO originally designed "Bobbin thread Taking up" assures "puckering free and consistent Top-stitching"
Also, originally designed "Pocket Folder" with vertical folding type promises "Pocket-corner sticking out free" completely.



"LED" TOUCH PANEL PROGRAMMER

with "LED" Touch Panel, **30** Patterns is programmable and allowed to select and convert the Pattterns simply. Sewing-end mode is allowed ----to "Triangle and Straight" mode freely. with CORRECTION , Pattern Size correction is allowed by "0.1mm"unit Also,available Expand/Reduction by "0.1mm unit"


ERROR---T.B.D.STOP, BOBBIN BALANCE COUNT ---is indicated in Red.

FREE CHOICE OF SEWING-END

available to select Sewing-end mode
---[Triangle or Straight]--- freely.
But, <u>NOT</u> allowed to convert Left/Right and
Bottom side.

But, variable Left/Right side only---NOT allowed Bottom part--- when Left/Right size only changes to smaller, Sewing Pattern Gauge is applicable---available with Soft programming and Pocket Setting Plate conversion.

when Left/Right and Bottom size is varied, PATTERN GAUGE conversion is required..





with PRSSER PAT, Fabric is fed to the Needle point without "slipping", and with NEEDLE FOOT PRSSER, finest Topstitching without "slipping, fluttering" is promised----even the Biginner is allowed "Skilless and High Productivities"



ROTATATE STACKER

with ROTATATE STACKER, Pocket bag is rotated rotated by **90°** and stacked on completely----after Sewing Cycle ends · · · supports "overlapped working" and "High-productivities". with <u>"XY"</u> Feeder, Tilting Head is allowed simply. Wide Maintennace variation is also applied.





