

NEW 『 E 』 TYPE

NEW SHORT SEAMER 1000



MODEL U-3307-E/1000

FLEXIBLE SEWING MODES **THREAD-BREAKAGE DETECTOR (T.B.D.)**

BOBBIN WINDER

With Photo-Sensor and Limit Switch operating, various sewing modes are applicable.

REGULAR SEWING MODES



T.B.D. detects accurately when thread is broken.



【 OPTION 】

SMALL PART SEWING MODES

Parts sewing is allowed successively. Stacking is NOT allowed.

Bobbin thread winding is allowed at any time. Bobbin idling is NOT permitted !



【 OPTIONAL DEVICES 】


【 OPTION 】

VARIABLE SEWING MODES

- 12 long size (2 ~ 3m or more) sewing
- 13 multiplied fabrics (3 pcs more) sewing
- 14 multiplied on the halfway
- 15 different fabrics (Knits/liner) sewing
- 16 differential curved fabrics sewing
- 17 "8mm" Basting
- 18 larger Skirt pleating
- 19 differential seam margin sewing

"L" TYPE SEWING MODE

Applicable to Men's Jacket Back-center and Skirt pleating. "L" type (90°) angle sewing is allowed automatically. With Breaker setting on the designed point, "L" sewing is allowed.



【 DEVICES 】

- ◆ PHOTO SENSOR/LIMIT SWITCH
- ◆ TWIN KEEPERS
- ◆ STRAIGHT RAIL with GAUGE (1 SET)
- ◆ ENDLESS SEWING CYCLE MODE
- ◆ RAIL PRESSER AT NEEDLE AREA
- ◆ VACUUM BLOWER MOTOR (200W)
- ◆ STACKER
- ◆ FLEXIBLE RAIL FEEDING STROKE
- ◆ AIR GUN

《 OPTION 》

- ◆ THREAD BREAKAGE DETECTOR (TBD)
- ◆ BOBBIN WINDER

【 DAILY OUTPUT 】

- ◆ 1,600seam per 8H 1 seam 12sec

Appearance & Specifications changeable for Modification ---without Notice !

《 SPECIFICATION 》

- MACHINE HEAD JUKI DDL-9000B
- SEWING LENGTH 5,000rpm
- SEWING LENGTH Max 1,050mm
- RAIL UP/DOWN 200mm
- TABLE HEIGHT 900mm
- POWER SUPPLY 200V/AC 950W
- AIR SUPPLY 5kg/cm 10N /min
- FLOOR SPACE L/2340 x W/940 x H/1300

YUHO SEWING MACHINE CO., LTD.

5-chome 3-1, Biwajima,
Nishi-ku, Nagoya,
Tel: +81-52-522-6276
Fax: +81-52-531-9270
e-mail: yuho@yuhomac.com
URL: <http://www.yuhomac.com>



NEW 『 E 』 TYPE

NEW SHORT SEAMER 1000

MODEL U-3307-E/1000

NEW



YUHO ORIGINARY DESIGNED GUIDE-RAIL CREATES THE FINEST "LONG SEAM LINE" AS DESIGNED PERFECTLY !!

WITH ORIGINALLY DESIGNED GUIDE RAIL FEEDING MECHANISM, FABRIC IS HELD DOWN TIGHTLY, AND ALLOWED AN EXCELLENT RUN-STITCHING FREE FROM "SEAM-FAIL, DISTORTION" COMPLETELY.

HIGH FLEXIBILITIES---MATCHING PLAIDS, SEWING WITH DIFFERENT TWO FABRICS, etc --- IS APPLICABLE.

WITH "LED" DISPLAY PANEL PROGRAMMED BY SEQUECE CONTROLLER, SIMPLIFIED AND OVERLAPPED WORKING PROMISES "HIGH PRODUCTIVITIES AND CONSISTENT SEWING".



YUHO SEWING MACHINE

NEW 『 E 』 TYPE


NEW SHORT SEAMER 1000

MODEL U-3307-E/1000






GUIDE RAIL FEEDING MECHANISM

Idle sewing feeds on at full speed to the Needle, and return at full speed after sewing end. Sewing speed is adjustable to the fabrics freely. With Photo-Sensor detection, sewing start and end are allowed automatically, freely. With "2" Breakers, sewing ends or starts on the halfway or sewing jump. Rail Presser at the Needle area supports free from Rail floating up. This promises consistent sewing at High speed 4,000rpm. After sewing end, fabric is stacked on automatically--- NO handling makes "overlapped working" and promises High Productivities.




GUIDE RAIL FEEDING ADVANTAGES

YUHO originally designed Guide Rail Feeding mechanism is accumulated and improved with the latest technologies "XY" Rail feeding (X/1050 mm-Y/140mm) follows to the curved seam line accurately. This advantages for Men's Ladies' Jackets seaming such as Center Vents, Side sleeves, etc--- specially, promises "Puckering, Seam failing" completely. YUHO Guide Rail Feeding is flexible to the various fabrics for Ladies---so thinner or so heavier. Guide Rail is set with Gauge accurately, removable simply with hand lever. With single Rail Pattern only, other different Patterns are applicable.



KEEPER AS LOADING SUPPORTER

Loading is just enough to place fabric on the working table. Simply movable all round Twin Keeper can clamp fabric along to seam line freely. This helps to load 2 or 3 different fabrics or attaching labels, easing. Additional Keepers are allowed upto ---4 sets---as "OPTION" Powerful Vacuuming suction supports loading accurately. When Vacuuming is NO need, use VACUUM ON/OFF SW. freely.




ENDLESS SEWING CYCLE MODE

This mode is applicable to extra longer fabrics sewing---such as Bed sheet covers, Curtains, etc. Additionally, extra big stitching pitch ---by 8mm is applicable flexibly. When Endless sewing mode runs, longer fabric stops on the halfway while Needle is sunken, and repeats it until Photo Sensor detects fabric-end. While Needle is sunken, sewing stops---makes free from "seam fail".



LED DISPLAY TOUCH PANEL

With LED DISPLAY PANEL touching, Switch operation and Maintenance, etc are allowed simply, quickly. Cycle counting, Bobbin thread counting can set on. When Bobbin thread gets near to "0", Panel displays in Red.



NEEDLE THREAD CLAMPER (patented No.1515029)

Thread Clamper clamps thread after thread trimming, and release when sewing starts automatically. For free from sewing start troubling, Thread Wiper wipes thread to absorb strong tension when Needle goes down. Clamping and releasing repeat every sewing cycle.



SMALL PART SEWING MODES

Parts sewing is allowed successively. Stacking is NOT allowed.

